

Self-service Kiosk | Vision S | HS330T

Key Features

- ☐ 23.8" True flat capacitive touch screen enhancing user experience
- ☐ Membership camera/Facial payment camera makes transactions easier
- ☐ Flexible operational scenarios; wall mount or floor stand
- Multi-modular design allowing for self-service or self-checkout customization to suit a variety of retail or hospitality environments
- ☐ Integrated glass panel, ultra-thin body, and round aluminum alloy frame make the machine more beautiful and fashionable.



MODEL			HS330T			
Processor			Qualcomm Snapdragon SDM660 with Kryo 260 8*cores 4 cores with 2.2Ghz; 4cores with 1.8Ghz			
Operating System			Android 12 (standard)			
Memory			4GB	standard	6GB	optional
Storage			64GB eMMC	Stanuaru	128GB eMMC	орионас
Display Panel			23.8inch TFT-LCD 16:9 Display resolution:1920*1080			
Touch Screen			True flat capacitive touch screen			
Power Supply			24V 90W power supply			
Integrated Scanner			Single window, support 1D/2D barcode Standard small scanner window type(1280*800 pixels) Optional big scanner window type(1280*1024 pixels)			
Integrated Printer			58/80mm thermal printer			
Speaker			5W 4R Speaker			
Wireless Connection			Dual-band Wi-Fi® 802.11a/b/g/n/ac 2.4/5GHz/ & BT 5.0 BLE			
I/O Ports			1* RJ45 , 100M/1000M Gigabit LAN port(in pole stand)			
			1* COM Port(in pole stand)			
		4* USB 2.0 Ports (3 on host side, 1 in pole stand)				
Dimensions (LxWxH)			1681*738*626mm			
Weight			30kg (Host + standstandard) 50kg (Host + stand + metal plate)			
Optional Peripheral s	Tra	nsaction camera	Face ID camera or Membership camera			
	Stand		Ground Stand			
			Big Metal plate(optional for no grounding screws)			
	Wall Mount		Wall mount bracket(for no stand)			
	Shelving Tray		Small shelving Tray(metal /plastic)			
			Big shelving Tray(metal /plastic)			
	Bracket		External Pinpad holder			
			Plastic bag holder			
	Security scale		60kg security scale			
Operating Voltage			110V/240V AC, 50-60hz			
Environment Operating Storage		Operating	5°C - 40°C/40%-60% RH non-condensing			
		-5°C - 50°C/30%-80% RH non-condensing				
EMC and Safety			CE/ FCC Pending			
Colour			Standard: White			



☐ Front opening door for easier maintenance


Patented protection lock, printer anti-theft design to prevent accidental touch





Shelving Unit optional

Disclaimer: All products specifications are subject to change without notice.





www.hics.histonetec.com

