

Key Features

- ❑ i3/i5 12/13 generation CPU provide powerful performance ;
- ❑ Die-cast aluminum housing for high reliable;
- ❑ With compact footprint and sleek design elements;
- ❑ Carries the full suite of multiple ports: USB2.0&USB3.0 , TypeC , Serial, Cash Drawer and Network LAN;
- ❑ Low-Profile, foldable base, Multiple Height Adjustments and VESA mount Capability(need VESA convertor);



MODEL	HK578A
Processor	Intel Alder Lake , Intel 12 th Gen CPU : Core i3 12gen Optional: Core i5 12gen, Core i3 13 gen, Cor i5 13gen.
Operating System	Windows 10/windows 11 /Linux
Memory	SO-DIMM DDR4 3200MHz 8GB,up to 32GB
Storage	2.5inch SATA SSD 128GB, up to 512GB
	Optional M.2 NVME/SATA 128GB, up 512GB
Display Panel	15" TFT LCD (LED back light) /4:3 /resolution: 1024 x 768
Touch Screen	True flat capacitive touch screen
Power Supply	24V 60W(standard) ; 24 90W/120W(for with 80mm printer)
Speaker	2*3W Speaker
I/O Ports(Standard)	7* USB: 2* USB 3.0; 5* USB 2.0 (included 1*24V Powered USB)
	1* Type C full function Port
	3* RJ50 COM Ports
	1* RJ45 100M/1000M Gigabit LAN
	1* HDMI for second display
	1* 24V Power-in
	1* 12V DC Output for second screen
	1* Audio,3.5mm
	1* 24V RJ11 for Cash drawer
I/O Ports(Optional)	7* USB: 2* USB 3.0; 5* USB 2.0 (included 1*24V Powered USB+ 2*12V PowerUSB)
	1* Type C full function Port
	2* RJ50 COM Ports
	1* RJ45 100M/1000M Gigabit LAN
	1* HDMI for second display
	1* 24V Power-in
	1* Audio,3.5mm
	1* 24V RJ11 for Cash drawer

MODEL		HK578A
Dimensions (LxWxH)		349x252x332 mm
Weight		5kg
Optional Peripherals	Card Reader	MSR only (3 tracks MSR)
		MSR+RFID (Supports MIFARE one and MIFARE CPU card)
	Fingerprint reader	Fingerprint reader
	Stand	Normal Desktop Stand
	Wall Mount	Wall mount bracket
	Second display	15" second screen / resolution: 1024*768(Touch/non-Touch)
		10.4" second screen / resolution: 800 x 600(Touch/non-Touch)
		2x20 characters VFD
wireless	Dual-band Wi-Fi® 802.11a/b/g/n/ac/ax 2.4GHz/5GHz , support WI-FI 6 BT5.0	
Environment	Operating	0°C - 40°C/20%-80% RH non-condensing
	Storage	-20°C - 60°C/10%-90% RH non-condensing
EMC and Safety		FCC /CE / RoHS
Tilt Adjustment		Single display: 0- 150° (Vertical) Dual display: 0-45° (Vertical)
Colour		Dark Gray



- Optional MSR
- Optional MSR+RFID
- Optional Fingerprint reader
- Optional 15" second display
- Optional 10.4" second display
- Optional VFD





- Dual hinge for flexible adjustment
- Die-cast aluminum housing for high reliable



Disclaimer: All products specifications are subject to change without notice.

QINGDAO HISTONE INTELLIGENT COMMERCIAL SYSTEM CO.,LTD.
Wisdom Valley,NO.8 Shengshui Road, Laoshan District, Qingdao City, China.
Tel: +86 (532) 66069168

 infopos@histonetec.com

 www.hics.histonetec.com

HiStone